

Bombas Sun Pumps

BOMBA SUMERGIBLE SIN ESCOBILLAS			1 HP		MODELO SCS 4 - 325	
PSI	CDT METROS	LPM	VOLTAJE CD MOTOR	CORRIENTE MOTOR	WATTS MOTOR	EFICIENCIA
0	0.0	17.0	60	3.93	236	0%
15	10.6	15.1	60	3.95	237	11%
30	21.1	13.1	60	3.94	236	19%
45	31.7	10.6	60	3.86	232	24%
60	42.3	7.2	60	3.69	221	22%
75	52.8	2.6	60	3.25	195	12%
90	63.4	0.0	60	2.93	176	0%

Controlador PCB120LM1

BOMBA SUMERGIBLE SIN ESCOBILLAS			1 HP		MODELO SCS 4 - 325	
PSI	CDT METROS	LPM	VOLTAJE CD MOTOR	CORRIENTE MOTOR	WATTS MOTOR	EFICIENCIA
0	0.0	20.4	75	5.11	383	0%
15	10.6	18.9	75	5.12	384	8%
30	21.1	17.2	75	5.13	385	15%
45	31.7	15.5	75	5.11	383	21%
60	42.3	13.6	75	5.06	380	25%
75	52.8	11.4	75	4.96	372	26%
90	63.4	8.7	75	4.77	358	25%
105	73.9	5.3	75	4.42	332	19%
120	84.5	0.0	75	3.74	281	0%

Controlador PCB120LM1

BOMBA SUMERGIBLE SIN ESCOBILLAS			1 HP		MODELO SCS 4 - 325	
PSI	CDT METROS	LPM	VOLTAJE CD MOTOR	CORRIENTE MOTOR	WATTS MOTOR	EFICIENCIA
0	0.0	24.2	90	6.29	566	0%
15	10.6	22.8	90	6.31	568	7%
30	21.1	21.4	90	6.32	569	13%
45	31.7	20.1	90	6.33	570	18%
60	42.3	18.5	90	6.30	567	23%
75	52.8	17.0	90	6.27	564	26%
90	63.4	15.1	90	6.20	558	28%
105	73.9	12.9	90	6.09	548	28%
120	84.5	10.7	90	5.92	533	28%
135	95.1	8.3	90	5.64	508	25%
150	105.6	5.7	90	5.25	473	21%
165	116.2	3.0	90	4.72	425	14%
180	126.8	0.0	90	4.51	406	0%

Controlador PCB120LM1

BOMBA SUMERGIBLE SIN ESCOBILLAS			1 HP	MODELO SCS 4 - 325		
PSI	CDT METROS	LPM	VOLTAJE MOTOR	CORRIENTE MOTOR	WATTS MOTOR	EFICIENCIA
0	0.0	27.3	105	7.45	782	0%
15	10.6	26.1	105	7.53	791	6%
30	21.1	25.0	105	7.53	791	11%
45	31.7	23.7	105	7.53	791	15%
60	42.3	22.3	105	7.52	790	20%
75	52.8	20.8	105	7.50	788	23%
90	63.4	19.3	105	7.47	784	25%
105	73.9	17.8	105	7.43	780	28%
120	84.5	16.3	105	7.35	772	29%
135	95.1	14.4	105	7.23	759	29%
150	105.6	12.5	105	7.08	743	29%
165	116.2	10.6	105	6.87	721	28%
180	126.8	8.3	105	6.59	692	25%
195	137.3	5.7	105	6.22	653	19%
210	147.9	3.0	105	5.76	605	12%
225	158.5	0.0	105	5.34	561	0%

BOMBA SUMERGIBLE SIN ESCOBILLAS			1 HP	MODELO SCS 4 - 325		
PSI	CDT METROS	LPM	VOLTAJE MOTOR	CORRIENTE MOTOR	WATTS MOTOR	EFICIENCIA
0	0.0	30.8	120	8.70	1044	0%
15	10.6	29.9	120	8.69	1043	5%
30	21.1	28.7	120	8.70	1044	9%
45	31.7	27.4	120	8.71	1045	14%
60	42.3	26.1	120	8.72	1046	17%
75	52.8	24.8	120	8.71	1045	20%
90	63.4	23.5	120	8.70	1044	23%
105	73.9	22.1	120	8.68	1042	26%
120	84.5	20.8	120	8.65	1038	28%
135	95.1	19.3	120	8.60	1032	29%
150	105.6	17.8	120	8.51	1021	30%
165	116.2	16.1	120	8.41	1009	30%
180	126.8	14.4	120	8.26	991	30%
195	137.3	12.5	120	9.09	971	29%
210	147.9	10.4	120	7.89	947	27%
225	158.5	8.1	120	7.59	911	23%
240	169.0	5.7	120	7.24	869	18%
255	179.6	3.0	120	6.85	822	11%
270	190.2	0.0	120	6.40	768	0%

Para mayor onformación escriba a: raruiz@syscom.com.mx

Bombas Sumergibles SUN PUMPS

Modelo SCS 4-325

